

Dozer Start-Up and Shut-Down

Equipment Required	Material Required	Personal Protective Equipment
Dozer	Diesel Fuel	CSA Approved Steel-toed Boots
	Grease	Hard-hat
	Appropriate Keys	Fully Clothed
	Appropriate Fluids	Safety Vest
		Eye and Ear Protection

Do not operate this equipment unless you are trained to do so and are familiar with the operating manual and the following job procedure. Company policy dictates that any or all equipment with any major safety deficiency must be immediately parked and tagged accordingly.

Start Up

1. Inspect the Dozer checking for oil leaks, damaged tracks, and vandalism.
2. Check all fluid levels before starting.
3. Check air filter and inspect that it is clean.
4. Lube all wear points. (Grease).
5. Turn on main battery disconnect switch.
6. Start dozer. (Use cold starting procedures if cold).
7. Check for any irregular sounds and any signs of repairs needed.
8. Check to make sure that blade properly goes up and down, tilts and angles.
9. Make sure tracks move freely and no excessive dirt/debris is built up in the tracks.

Shut Down

1. Fill up dozer with diesel fuel.
2. Remove all garbage (coffee cups and lunch material) and any loose objects
3. Inspect any excessive wear on machine.(Ie. Blade)

Fill out an “equipment repair form” reporting any work that needs to be completed on the equipment and return to Foreman.