

### Walk Behind Road Saw Start-Up and Shut- Down Procedures

Equipment Required	Material Required	Personal Protective Equipment
Husqvarna FS 524	Appropriate Fluids	Safety Vest
		CSA Approved Steel-Toed Boots
		Hard-Hat and Gloves
		Ear and Eye Protection

Do not operate this equipment unless you are trained to do so and are familiar with the operating manual and the following job procedure. Company policy dictates that any or all equipment with deficient brakes must be immediately parked and tagged accordingly.

#### Start Up

1. Inspect the Husqvarna FS 524 and check all fluid levels and top up as necessary. (Gas, water etc).
2. Check air filter. If dirty, blow clean with compressed air or replace if needed.
3. Inspect blade(s). (Use correct blade for application. Refer to owner’s manual). Remove nut off blade housing and install blade. Spin locking nut on to housing and tighten with wrench. (Please note on right hand side mount the housing is left hand tread!!).
4. Attach water source to saw blade housing. (IF in tight spots or only cutting a small amounts use water tank on top of saw. If cutting longer cuts, use hose directly from water source/water tote.
5. Make sure the saw is in neutral position or saw will not start. Use cold starting procedures and start engine making sure no personnel is close to saw. (Once saw starts the blade will spin).
6. Cut only asphalt or concrete with floor/road saw. Follow cutting procedures in operators manual.

#### Shutdown

1. After cutting turn, off saw in a safe location.
2. Remove blade and store away safely in truck or trailer. Wrap up all hoses and store in trailer/truck.
3. Clean off excessive debris and mud off machine.
4. Put Husqvarna saw back into trailer and properly strap down for transport.
5. Fill out an “equipment repair form” reporting any work that needs to be completed on the equipment and return to Foreman.